



BENCH MULTIMETERS



GDM8351

- True RMS measurements:
 - DC level only
 - AC RMS level only
 - AC + DC RMS
- Remote control from PC
- Ohmmeter 2 & 4 wires
- dBm, dB, Max Min, compare, store
- Math functions : ax + b, 1/x, %
- **Auxiliary display for Hz, dB, ripple**
- Option SC1 :16 channels scanner SC1



GDM8341

- **Dual display at the user's choice**
- True RMS measurements:
 - DC level only
 - AC RMS level only
 - AC + DC RMS
- High accuracy
- Continuity up to 500Ω
- **USB**

REF.	GDM8351	GDM8341
Display	120.000 counts	51.000 counts
Converter	TRMS AC+DC	
Bandwidth	100kHz	
VDC	100mV to 1000V	500mV to 1000 V
VAC	100mV to 750V	500mV to 750 V
IDC	10mA - 10A	500μA to 10A
IAC	10mA - 10A	500μA to 12A
OHM	100Ω to 100MΩ	500Ω to 50MΩ
Farad	10nF to 100μF	5nF to 50μF
Frequencymeter	10Hz to 1MHz	10 Hz - 1MHz
Diode test ()))	Max voltage : 6V Beeper	Max voltage: 1,5V. Buzzer <5Ω
°C (type K)	-200 to 300°C type J, K, T	
Ranging	Auto & Manual	
Interface	RS232 - USB	USB
Protection	CEI1010 CATIII 300Vrms pol2	
Power source	115- 230VAC 50/60Hz	100- 240VAC 50/60Hz
Dimensions / Weight	265 x 107 x 302mm / 2,9kg	265 x 107 x 302mm / 2,9kg
Supplied with	PC software & Driver Labview User's manual	PC software & User's manual