

DC & AC RMS Clamp + Wattmeter AC+DC RMS



10 000 COUNTS

- Autoranging
- Ohm - Continuity
- RMS AC+DC power measurement
- VAC & IAC TRMS measurements
- Peak hold function : Max
- Autopower off after 30mn
- Test leads, soft carry case, battery
- CEI1010 CAT III 600Veff Pol2

Ref.	MS232				
IDC	600.0A	(1.5% + 5dgt)	(1.8% + 5dgt)		
IAC RMS	600.0A	(1.5% + 5dgt from 50 to 500Hz)	(2% + 5dgt 50Hz)		
VDC	600.0V	(1% + 5dgt)	(1.5% + 3dgt)		
VAC RMS	600.0V	(1.5% + 5dgt from 50 to 500Hz)	(1.8% + 5dgt 50Hz)		
OHM	10 000Ω	(1% + 5dgt)	(1.5% + 2dgt)		
.J))	Ring for R< 100Ω				
Diode					
WDC	100.00 kW - 360.0kW	(2% + 5dgt)			
W RMS AC+DC	100.00 kW - 360.0kW	(2.5% + 5dgt)			
Hz	(1.2% + 2dgt)				
Dimensions	218 x 84 x 30 mm / 270g				
Jaw opening	Ø 30mm				

The clamps with the PWM logo
are compatible with PWM variators.

PWM