



## 70 to 200MHz hand-held oscilloscope multimeter with touchscreen



USB

Labview Driver

PC software

- Touchscreen 7" (480 x 800).
- 3 versions : 70Mhz, 100Mhz and 200Mhz - 1Mpoints or 5Mpoints.
- Data save on USB key.
- Internal battery.
- Multimeters functions.

REF.	GDS207	GDS210	GDS220	GDS307	GDS310	GDS320
Channels	2	2	2	2	2	2
Bandwidth -3dB	70MHz	100MHz	200MHz	70MHz	100MHz	200MHz
Rise time	<5ns	<3.5ns	<1.75ns	<5ns	<3.5ns	<1.75ns
Sampling rate	1 Gsa/s					
Record length by channel	1Mpoints			5Mpoints		
Sensitivity	2mV/div to 10V/div					
Modes	Auto - Normal - Single - Force					
Fonctions Math - FFT	Via the software					
Auto-measurement	36					
Measurement cursors	$\Delta V$ , $\Delta T$ , Frequency					
Autoset functions	yes					
Interface	USB					
Temperature	no			-50°C à 1000°C (probe in option)		
Multimeter	VDC - VAC - IDC - IAC - $\Omega$ - Test diodes - Continuité <15 $\Omega$					
Power source	Li-polymer 6100mAh - 7,4V. Operation time 4 Hours. Charge time 75% 2 hours.					
Dimensions / Weight	240 x 136 x 60mm / 1.5kg					
Supplied with	2 oscilloscope probes / 2 test leads for multimeter / Mains adaptor Software / Transport case / User's manual.					