

PORTABLE SOLAR POWER UNIT TYPE RESTITUTION NETWORK



Dims du panneau :
1600 x 800 x 100mm

Dims du panneau :
1600 x 800 x 100mm



Dims de la malette : 580 x 460 x 205mm

This learning case allows the study of the return of photovoltaic energy on the national 230VAC 50Hz grid.

You can choose between two types of operation:

- total return of the energy produced
- return of the energy not consumed only.

A silkscreen represents the different components.

The components are to be connected with safety cables.

This case must be connected to a 45Vmin photovoltaic voltage source.

Input voltage between 45VDC and 150VDC.

EDUCATIONAL OBJECTIVES

- Discover the different elements of a photovoltaic installation network restitution.
- Apprehend and understand the security elements present.
- Perform electrical measurements of the various quantities.
- Analyze & interpret the results.
- Study the performance and the effects related to the positioning of the panels
- Study the energy chain (production, use, resale, energy behavior).
- Wiring a photovoltaic installation with grid restitution.

STUDENT + TEACHER PEDAGOGICAL FILE

Composition of the technical case

- Impact resistant polypropylene case. It can be closed without unwiring the safety cords from the front panel. Lightweight and easily transportable using its handle.
- 2 photovoltaic connectors for connecting solar panels.
- 1 surge arrester.
- 1 bipolar fuse holder with gPV cartridge protecting the solar panel circuit and use.
- 1 disconnector to isolate the circuit of the solar panels from the technical case.
- 1 UPS 500W synchronizable on the network
- 1 On / Off switch for maintenance.
- 3 energy meters
- 1 disconnector to isolate the connection to the network.
- 1 voltage controller
- 1 bipolar 30mA differential circuit breaker
- 1 230VAC-500W 50Hz output on 4mm safety terminals
- 1 230VAC-500W 50Hz output on electrical outlet
- Dimensions: 580 x 460 x 205mm

Supplied with an educational file including

- A theoretical reminder on the different types of cells and photovoltaic energy.
- The detailed wiring diagram of the solar power plant.
- Complete theoretical and practical practical work in student / teacher notebook form.
- Complete instructions for each component.

ref. SOL-RES

The SOL-RES solar power plant includes:

- 1 technical case.
- 2 photovoltaic panels on tilting frames of approximately 200Wp each.
- 1 solar cable 30 m to connect the panels to the case.
- 2 portholes with 60W lamps to observe consumption.
- 1 set of safety cords.
- 1 power cord.

Features of the panel

- Open circuit voltage: 46VDC
- Short-circuit current: 6.3A
- Optimum operating voltage: 37VDC
- Optimum operating current: 5.7A
- Maximum power: 215Wc (variation of $\pm 10\%$ depending on the series)
- Sealed connections IP65 – 1000V on the rear of the panel.
- Type of cells: Monocrystalline silicon

Features of the frame

- Robust aluminum frame.
 - Useful surface area of the cells 1.5m².
 - Device for measuring the tilt angle
 - Tilt adjustable from 5° to 70°
 - Two ball joints with clamping levers for positioning the panel to the required tilt angle.
 - Several SOL-200 can be coupled electrically to increase power.
 - Light and easy to move.
- Dimensions Folded position: 1600 x 800 x 100mm - Weight 27kg ($\pm 10\%$ depending on the series)