



AC/DC PORTABLE POWER SUPPLY

Adjustable from 0 to 230V in DC or AC, this power supply delivers a constant current of 3A. Protected by a thermal-magnetic circuit breaker, the safety of users is ensured by the separation of circuits.

- | | |
|---|--|
| <ul style="list-style-type: none"> • Mains input • On/Off • DC variable output • AC variable output • Variable voltage setting • Max current DC or AC • Output displays • Input protection • Output protection • User's safety • DC output smoothing • AC/DC commutation • Connecting • Dimensions / Weight | <ul style="list-style-type: none"> Mains cable General luminous switch 0-240 V 0-230 V rotating knob onto the unit 3A 1 voltmeter and 1 ammeter by time delay fuse thermal-magnetic circuit-breaker all outputs are insulated from mains by capacitors, without electronic regulation CC - 0 - CA by rotary switch Safety terminals 4mm 210 x 245 x 350mm / 14kg |
|---|--|

COMPATIBLE WITH 300W MOTORS

ref. ISOSEC1



DUAL DC PORTABLE POWER SUPPLY

This power supply includes :
 - one variable DC supply with voltmeter & ammeter
 - one fixed DC supply
 Protection of users is ensured by galvanic insulation of outputs.

- | | |
|---|--|
| <ul style="list-style-type: none"> • Mains : • On/Off : • DC variable output : • DC fixed output : • Input protection : • Output protection : • Smoothing : • Dimensions / weight : | <ul style="list-style-type: none"> Mains cable General switch and light 0-240V / 3A 230V / 1A by time delay fuses by thermal magnetic circuit-breakers by capacitors 210 x 245 x 350mm / 20kg. |
|---|--|

COMPATIBLE WITH 300W MOTORS

ref. ISOSEC2