

## Variable autotransformers

These variable autotransformers are available in 3 designs.

- Bare for references finishing with a "N"
- With a stainless steel case for references finishing with "A" or "P"
- Protected by a case, fitted with 4 casters, circuit breaker and ON/OFF LED for references finishing with a "PE"

Covered (P and PE) units have a mains cable at the primary and safety terminals at the secondary.

### BARE DESIGN



Single-phase						
Ref	Power	Primary	Secondary	Secondary	Weight	Dims mm
ALT5N	1.25kVA	220/240V	0-250V	5A	5,2kg	151 x 151 x 123mm
ALT7N	1.85kVA	220/240V	0-260V	7A	7,7kg	175 x 175 x 123mm
ALT13N	3.38kVA	220/240V	0-260V	13A	13,3kg	233 x 233 x 123mm
VAR92N	5.20kVA	220/240V	0-260V	20A	16kg	294 x 294 x 145mm

Three-phase						
Ref	Power	Primary	Secondary	Secondary	Weight	Dims mm
TRT5N	3.72kVA	380/400V	0-430V	5A	19kg	155 x 155 x 407mm
TRT8N	6.23kVA	380/400V	0-450V	8A	27kg	181 x 181 x 407mm
TRT13N	10.13kVA	380/400V	0-450V	13A	39kg	233 x 233 x 422mm
3VAR92N	15.60kVA	380/400V	0-450V	20A	56kg	310 x 310 x 402mm



ALT5N

### COVER DESIGN - PRIMARY ON MAINS CABLE



TRT30A

Single-phase						
Ref	Power	Primary	Secondary	Secondary	Weight	Dims mm
ALT5A*	1.25kVA	220/240V	0-250V	5A	6.2kg	Ø170 x 157mm
ALT7A*	1.85kVA	220/240V	0-260V	7A	8.8kg	Ø202 x 157mm
ALT13A*	3.28kVA	220/240V	0-260V	13A	13.5kg	Ø268 x 157mm
ALT15A	3.90kVA	220/240V	0-260V	15A	22kg	286 x 286 x 200mm
VAR92P	5.20kVA	220/240V	0-260V	20A	19kg	350 x 320 x 550mm

\* fuses at secondary

Three-phase						
Ref	Power	Primary	Secondary	Secondary	Weight	Dims mm
TRT8A	6.23kVA	380/400V	0-450V	8A	33kg	200 x 200 x 468mm
TRT13A	10.13kVA	380/400V	0-450V	13A	48kg	286 x 286 x 468mm
TRT30A	23.38kVA	380/400V	0-450V	30A	92kg	450 x 450 x 700mm



ALT5A



ALT15A

### COVER DESIGN WITH CIRCUIT BREAKERS & LIGHT - PRIMARY ON MAINS CABLE



TRT8-PE

Single-phase						
Réf	Power	Primary	Secondary	Secondary	Weight	Dims mm
ALT5-PE	1.25kVA	220/240V	0-250V	5A	8.9kg	230 x 140 x 250mm
ALT7-PE	1.85kVA	220/240V	0-260V	7A	11.5kg	230 x 140 x 250mm
ALT13-PE	3.28kVA	220/240V	0-260V	13A	14.6kg	230 x 140 x 250mm

Three-phase						
Ref	Power	Primary	Secondary	Secondary	Weight	Dims mm
TRT5-PE	3.72kVA	380/400V	0-430V	5A	30kg	280 x 340 x 510mm
TRT8-PE	6.23kVA	380/400V	0-450V	8A	37kg	280 x 340 x 510mm
TRT13-PE	10.13kVA	380/400V	0-450V	13A	48kg	280 x 340 x 530mm
3VAR92P	15.60kVA	380/400V	0-450V	20A	71kg	350 x 360 x 600mm

Modes on wheels



ALT5-PE